

Material Safety Data Sheet

DIESEL FUEL ADDITIVE

05/25/06

Alt, Inc.

3000 SW 42nd Avenue, Palm City, FL 34990

InfoTrac:

Catalog Number: MSDA

Telephone: (772) 287-9280

Emergency: (800) 535-5053

International: (800) 535-5053

A. Product Identification

Synonyms: ALKYLAMINES

Chemical Name: Mixture

Chemical Family: Hydrocarbons

Chemical Formula: Mixture

CAS Reg. No.: 68955-53-3

Product No.: 042503B

Product and/or Components Entered on EPA's TSCA Inventory: YES

This product is in U.S. commerce, and is listed in the Toxic Substances Control Act (TSCA) Inventory of Chemicals; hence, it may be subject to applicable TSCA provisions and restrictions.

B. Components

<u>Ingredients</u>	<u>CAS Number</u>	<u>% By Wt.</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
Paraffinic hydrocarbons	64742967	> 55	NE	NE
Olefinic hydrocarbons	Various	< 5	NE	NE
Aromatic hydrocarbons	Various	> 27	NE	NE
may include Benzene	71432	< 50 ppm	1 ppm*	10 ppm
Borates	5419-55-6	< 5,000ppm		

* Work operations exempted by the Benzene Standard, 29 CFR 1910.1028, will have a 10 ppm 8 hour TWA .

C. Personal Protection Information Ventilation: Use adequate ventilation.

Respiratory Protection: Not generally required unless needed to prevent respiratory irritation. In case of spill or leak resulting in unknown concentration, use NIOSH/MSHA approved supplied air respirator.

Eye Protection: For splash protection, use chemical goggles and face shield.

Skin Protection: Use gloves resistant to the material being used. (ie. neoprene or Nitrile rubber). Use protective garments to prevent excessive skin contact.

NOTE: Personal protection information shown in Section C is based upon general information as to normal uses and conditions. Where special or unusual uses or conditions exist, it is suggested that the expert assistance of an industrial hygienist or other qualified professional be sought.

D. Handling and Storage Precautions:

Do not get in eyes, on skin or on clothing. Avoid breathing vapors, mist, fume or dust. Do not swallow. May be aspirated into lungs. Wear protective equipment and/or garments described in Section C if exposure conditions warrant. Wash thoroughly after handling. Launder contaminated clothing before reuse. Use with adequate ventilation. Keep away from heat, sparks, and flames. Store in a Well ventilated area. Store in a closed container. Bond and ground during transfer.

E. Reactivity Data Stability:	Stable
Conditions to Avoid:	Not Established
Incompatibility (Materials to Avoid):	Oxygen and strong oxidizing agents
Hazardous Polymerization:	Will not occur
Conditions to Avoid:	OPEN FLAME, TEMPS OVER 120 F.
Hazardous Decomposition Products:	Carbon and sulfur oxides and hydrocarbons formed when burned.

F. Health Hazard Data :

Recommended Exposure limits: Not Established, may cause defatting of the skin, resulting in dermatitis. Dermal LD50 for diesel fuel is > 5 ml/kg (rabbit).

Inhalation: May cause irritation to nose, throat or lungs. Headache, nausea, dizziness, unconsciousness may occur. CONSULT PHYSICIAN IMMEDIATELY.

Ingestion: May cause irritation to intestines. May cause headache, nausea, unconsciousness. If swallowed, may be aspirated resulting in inflammation and possible fluid accumulation in the lungs. Oral LD50 for diesel fuel is 9 ml/kg (rat).

Subchronic and Chronic Effects of Overexposure:

Combustion, a normal use of diesel fuel, results in an exhaust that has been associated with lung cancer in animals. There is limited evidence to suggest an association between occupational exposure to diesel exhaust and lung cancer in humans. Carbon monoxide inhalation may cause carboxyhemoglobinemia. Chronic exposure to carbon monoxide causes fatigue, poor memory, loss of sensation in fingers, visual disturbances and insomnia. Carboxyhemoglobinemia is frequently misdiagnosed as flu. Sensitive subpopulations to the inhalation of carbon monoxide exist. Carbon monoxide displaces oxygen in the bloodstream and therefore, can adversely effect people with preexisting heart disease, pregnant and smokers.

Other Health Effects: No known applicable information.

Health Hazard Categories:

	Animal	Human		Animal	Human
Known Carcinogen	___	___	Toxic	___	___
Suspect Carcinogen	___	___	Corrosive	___	___
Mutagen	___	___	Irritant	<u> X </u>	<u> X </u>
Teratogen	___	___	Target Organ Toxin	<u> X </u>	<u> X </u>
Allergic Sensitizer	___	___	Specify Lung Aspiration Hazard		
Highly Toxic	___	___			

First Aid and Emergency Procedures:

Eye: Flush eyes with running water for at least fifteen minutes. If irritation or adverse symptoms develop, seek medical attention.

Skin: Immediately wash skin with soap and water for at least fifteen minutes. If irritation or adverse symptoms develop, seek medical attention.

Inhalation: Remove from exposure. If breathing is difficult, give oxygen. If breathing ceases, administer artificial respiration followed by oxygen. Seek immediate medical attention.

Ingestion: Do not induce vomiting. Seek immediate medical attention.

Note to Physician: Gastric lavage using a cuffed endotracheal tube may be performed at your discretion.

G. Physical Data

Appearance:	Pale yellow liquid
Odor:	Mild
Boiling Point:	200 F.
Vapor Pressure:	(mm Hg.) 0.40
Vapor Density (Air = 1):	>3
Solubility in Water:	None
Specific Gravity (H ₂ O = 1):	0.85 at 60/60F (16/16C)
Percent Volatile by Volume:	100
Evaporation Rate (Butyl Acetate=1):	<1
Viscosity:	32.6-40.0 SuS @ 100 deg.F.

H. Fire and Explosion Data

Flash Point (Method Used): > 181 F >

Flammable Limits (% by Volume in Air): LEL Not Established UEL Not Established

Fire Extinguishing Media: Dry chemical, foam or carbon dioxide CO₂ personnel. Shut off source, if possible. Use NIOSH/MSHA approved self contained breathing apparatus and other protective equipment and/or garments described in Section C if conditions warrant. Water fog or spray may be used to cool exposed containers and equipment. Do not spray water directly on fire will float and could be reignited on surface of water.

Fire and Explosion Hazards: Carbon and sulfur oxides and various hydrocarbons formed when burned.

I. Spill, Leak and Disposal Procedures Precautions Required if Material is Released or Spilled:

Evacuate area of all unnecessary personnel. Wear protective and/or garments described in Section C if exposure conditions warrant. Shut off source, if possible and contain spill. Protect from ignition. Keep out of water sources and sewers. Absorb in dry, inert material (sand, clay, etc.). Transfer to disposal drums using non sparking equipment.

Waste Disposal (Insure Conformity with all Applicable Disposal Regulations): Incinerate or place in permitted waste management facility.

J. DOT Transportation

Shipping Name: chemical
DOT: Non Regulated
ID Number:
Marking: None
Label: None
Placard: None
Hazardous Substance/RQ: Not applicable
Shipping Description: Chemical
Packaging References: This product is unregulated by DOT when shipped in non bulk quantities.

K. RCRA Classification Unadulterated Product as a Waste Ignitable (D001) Prior to disposal, consult your environmental contact to determine if TCLP (Toxicity Characteristic Leaching procedure, EPA Test Method 1311) is required. Reference 40 CFR Part 261.

L. Protection Required for Work on Contaminated Equipment Contact immediate supervisor for in Section C if exposure conditions warrant.

M. Hazard Classification

This product meets the following hazard definition(s) as defined by the Occupational Safety and Health Hazard Communication Standard (29 CFR Section 1910.1200):

<input checked="" type="checkbox"/> Combustible Liquid	<input type="checkbox"/> Flammable Aerosol	<input type="checkbox"/> Oxidizer
<input type="checkbox"/> Compressed Gas	<input type="checkbox"/> Explosive	<input type="checkbox"/> Pyrophoric
<input type="checkbox"/> Flammable Gas	<input checked="" type="checkbox"/> Health Hazard (Section F)	<input type="checkbox"/> Unstable
<input type="checkbox"/> Flammable Liquid	<input type="checkbox"/> Organic Peroxide	<input type="checkbox"/> Water Reactive
<input type="checkbox"/> Flammable Solid		

Based on information presently available, this product does not meet any of the hazard definitions of 29 CFR Section 1910.1200.

N. Additional Comments: SARA 313, This product contains the following chemical or chemicals subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372. (See Section B). Benzene

ALT Inc. believes that the information contained herein (including data and statements) is accurate as of the date hereof. NO WARRANTY OF MERCHANTABILITY, FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE AS CONCERNS THE INFORMATION HEREIN PROVIDED. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use of the product and information referred to herein are beyond the control of ALT Inc. expressly disclaims any and all liability as to any results obtained or arising from any use of the product or such information. No statement made herein shall be construed as a permission or recommendation for the use of any product in a manner that might infringe existing patents.