

Mike Phelps
Advanced Lubrication Tech.
6345 Balboa Blvd, Bldg III
Suite 350
Encino, CA 91316

12/07/2000
13:10:46
ALTEMP

Laboratory : 600759 Date: 11/27/2000
Description: DIESEL FUEL LUBRICITY

Test Performed	Proc-Rev	Result
Oxidation Stability, ASTM D2274-94.....	2274-1.2	5.0 mg/100mL
Copper Corrosion @50 deg.C, ASTM D130-94	0130-3.2	1A 3 Hours

We needed to mix the 150 ppm and the 200 ppm formulations together to get enough volume for the oxidation test. We mixed them 50/50. This would make the mix a 175 ppm treat rate for this test only. The oxidation stability value is very high. Industry accepted standard is 2.0 mg/100ml.

Copper Corrosion is a PASS. No tarnish (corrosion) was observed. See attached Falex report.

Respectfully Submitted,
Herguth Laboratories, Inc.

by Paul D. Herguth

cc: Herguth File Copy
Charles Foscue

Herguth File Copy
Advanced Lubrication Tech.
6345 Balboa Blvd, Bldg III
Suite 350
Encino, CA 91316

12/07/2000
13:10:46
ALTEMP

Laboratory : 600759 Date: 11/27/2000
Description: DIESEL FUEL LUBRICITY

Test Performed	Proc-Rev	Result
Oxidation Stability, ASTM D2274-94.....	2274-1.2	5.0 mg/100mL
Copper Corrosion @50 deg.C, ASTM D130-94	0130-3.2	1A 3 Hours

We needed to mix the 150 ppm and the 200 ppm formulations together to get enough volume for the oxidation test. We mixed them 50/50. This would make the mix a 175 ppm treat rate for this test only. The oxidation stability value is very high. Industry accepted standard is 2.0 mg/100ml.
Copper Corrosion is a PASS. No tarnish (corrosion) was observed. See attached Falex report.

Respectfully Submitted,
Herguth Laboratories, Inc.

by Paul D. Herguth

cc: Mike Phelps
Charles Foscue

HERGUTH FILE COPY

Charles Foscue
Advanced Lubrication Tech.
6345 Balboa Blvd
Suite 350
Encino, CA 91316

12/07/2000
13:10:46
ALTEMP

Laboratory : 600759 Date: 11/27/2000
Description: DIESEL FUEL LUBRICITY

Test Performed	Proc-Rev	Result
Oxidation Stability, ASTM D2274-94.....	2274-1.2	5.0 mg/100mL
Copper Corrosion @50 deg.C, ASTM D130-94	0130-3.2	1A 3 Hours

We needed to mix the 150 ppm and the 200 ppm formulations together to get enough volume for the oxidation test. We mixed them 50/50. This would make the mix a 175 ppm treat rate for this test only. The oxidation stability value is very high. Industry accepted standard is 2.0 mg/100ml.
Copper Corrosion is a PASS. No tarnish (corrosion) was observed. See attached Falex report.

Respectfully Submitted,
Herguth Laboratories, Inc.

by Paul D. Herguth

cc: Mike Phelps
Herguth File Copy